

MINI SCISSOR LIFTS

Easy UP 5 SP

INDOOR AND OUTDOOR USE

STANDARD EQUIPMENT

- Manual emergency lowering device
- Battery charger with automatic switch-off
- Low battery alert
- Battery switch-off
- Inclinometer with cut out and alarm
- Load sensor with audible/visual motion cut out and alarm
- Electrical scissor protection
- Non marking tires
- Cylinder holding valve
- Non-slip deck surface
- Full height access gate with spring-lock
- 2WD traction, DC electric motors
- Electromagnetic brakes on the 2WD
- Swivel caster interlock for straight line driving
- Pothole protection
- Control box on platform IP65, with proportional joystick and emergency stop
- Selector for 3 different proportional speed
- Audible motion alarm
- Horn
- Ground control panel with key switch
- Flashing beacon



5,2 m
working height

		EASY UP 5 SP
Number of scissors		3
A	mm	3200
B	mm	5200
C	mm	25
D	mm	1810
E	mm	710
Capacity (including 1 person)	kg	200
Electric motor (power pack)	kW	2
Electric drive motors	V/kW	24/1
Battery	V/Ah	2 x 12/105
Battery charger	V	230
Oil tank capacity	Lt.	2
Lifting time	s	17/20
Max side/longitudinal tilt angle	degrees	1,5/2,5
Gradeability	%	25
Traction speed	Km/h	0-4
Safety traction speed	Km/h	0,6
Internal turning radius	m	0
External turning radius	m	1,25
Total weight	Kg	500

